

THERMa-PUR™ Style 4122

THERMa-PUR™ is a proprietary new gasketing material designed for use in high temperature sealing applications. It is produced using an environmentally friendly solvent-free process and combines a unique formulation with a patent-pending fiber core. THERMa-PUR™ is yet another innovative Garlock Sealing Technologies sealing solution that provides more than just temperature resistance.

VALUE & BENEFITS

- » Extreme Temperature Able to withstand high temperature, whether continuous or in thermal cycling conditions
- » Oxidation Resistance Contains proprietary materials that provide improved weight loss characteristics over other high temperature solutions. (see graph)
- » Hydrophobic & Electrically Insulating Resists water and provides electrical isolation thus reducing the possibility of corrosion between flanges made of dissimilar metals
- » Easy Release from Flanges Does not stick to flanges making removal of gaskets easy and fast
- » Safer Handling Patent-pending fiber core makes gaskets safer to handle when compared to traditional high temperature gaskets with steel cores

IDEAL FOR


- » Marine and Land-based Exhaust Systems
- » Biomass Gasification Process
- » Oil and Gas Production
- » Mineral and Fertilizer Processing
- » Incineration Process
- » Co-generation Systems
- » Turbochargers Equipment
- » Process Drying Equipment



Cut Gaskets (4122-FC)



Corrugated Metal Gasket
(4122-CMG)



Kammprofile
(4122-KAMM)

THERMa-PUR™ EXTREME TEMPERATURE GASKETING

TYPICAL PHYSICAL PROPERTIES

Temperature	Continuous max.	+1832°F (1000°C)
Pressure ¹	psig (bar)	4122-FC
		500 (34.5)
		4122-CMG
		1000 (68.9)
		4122-KAMM
		Equal to flange rating
P x T, max. ²		4122-FC
		150,000 (5,100)
		4122-CMG
		600,000 (21,500)
		4122-KAMM
		Equal to flange rating

Typical Physical Properties for 4122-FC*:

ASTM Test Method F36

Compressibility, range, %	35-45
Recovery %	18

ASTM F38

Creep Relaxation, %	25
---------------------	----

ASTM F152

Tensile, w/insert, psi (N/mm ²)	1,200 (8.3)
---------------------------------------------	-------------

ASTM F1315

Density, lbs./ft ³ (grams/cm ³)	85 (1.36)
--------------------------------------------------------	-----------

ASTM D149

Dielectric Properties, volts/mil.	100
-----------------------------------	-----

NOTES:



1. Based on ANSI RF flanges at our preferred torque. When approaching maximum pressure, continuous operating temperature, minimum temperature or 50% of maximum P x T, consult Garlock Engineering.

2. P x T = psig x °F (bar x °C)

* This is a general guide and should not be the sole means of selecting or rejecting this material. ASTM test results in accordance with ASTM F-104; properties based on 1/16" (1.6mm) gasket thickness unless otherwise mentioned.


OUT PERFORMS

THERMa-PUR™ outperformed vermiculite based gaskets in laboratory testing[†]. THERMa-PUR™ showed significantly less leakage even in extreme thermal cycling condition[†]. For test details, please contact Garlock Engineering



LOW WEIGHT LOSS

THERMa-PUR™ proprietary formulation resists oxidation and has improved weight loss property by almost 2X when compared to other high temp organic based gaskets such as graphite and vermiculite



GSK 3:78

GARLOCK

an *EnPro* Industries family of companies

Tel: 1-877-GARLOCK / 315.597.4811

Fax: 800.543.0598 / 315.597.3216

www.garlock.com

Garlock Sealing Technologies

Garlock Rubber Technologies

GPT

Garlock PTY

Garlock do Brasil

Garlock de Canada, LTD

Garlock China

Garlock Singapore

Garlock Germany

Garlock India Private Limited

Garlock de Mexico, S.A. De C.V.

Garlock New Zealand

Garlock Great Britain Limited

Garlock Middle East